

TECHNI CONNECT 02 FR

Includes NATO STOCK NUMBER for HOSE -02-04-102FR: 4720-00-007-0422



Operating Temperature Range:

- 20 / + 90 C°

Features:

- Good resistance to mechanical damage
 - Robust
 - Highly flexible, compressibility: 1:8 ratio
- External galvanised steel helix protects against abrasion
 - Stronger than Techni Connect 01

For use in:

- Air conditioning
- Suction plants
- Ducting and extraction of air
- Tent ventilation / Heating
- Weld fume extraction
- Low pressure applications
- In areas with raised safety requirements

Length: 5 metres (10 metres on application)

PART CODES: SIZES & TECHNICAL SPECIFICATIONS

PRODUCT CODE	INNER DIAMETER	WORKING PRESSURE	VACUUM	BENDING RADIUS	WEIGHT
	<i>mm</i>	<i>bar</i>	<i>bar</i>	<i>mm</i>	<i>gr./mt.</i>
02-01-90FR	90	0,548	0,11	62	0,800
02-01-102FR	102	0,493	0,09	68	0,800
02-01-112FR	112	0,467	0,076	74	0,900
02-01-127FR	127	0,319	0,06	83	1,000
02-01-133FR	133	0,266	0,057	86	1,000
02-01-140FR	140	0,238	0,051	92	1,000
02-01-152FR	152	0,205	0,046	98	1,100
02-01-160FR	160	0,192	0,041	104	1,200
02-01-180FR	180	0,154	0,034	116	1,200
02-01-203FR	203	0,133	0,03	128	1,400
02-01-229FR	229	0,107	0,026	143	1,600
02-01-254FR	254	0,088	0,023	183	1,800
02-01-280FR	280	0,069	0,02	201	2,100
02-01-305FR	305	0,056	0,019	218	2,300
02-01-315FR	315	0,052	0,009	229	2,300
02-01-356FR	356	0,043	0,006	253	2,700
02-01-406FR	406	0,034	0,005	287	3,300
02-01-457FR	457	0,031	0,004	369	3,800
02-01-508FR	508	0,029	0,003	408	4,300
02-01-559FR	559	0,026	0,002	446	4,800
02-01-610FR	610	0,025	0,002	489	5,300
02-01-710FR	710	0,018	0,001	567	6,200
02-01-820FR	820	0,010	0,001	646	7,100
02-01-920FR	920	0,006	0,001	728	8,000
02-01-1030FR	1030	0,004	0,001	810	8,900
02-01-1130FR	1130	0,002	0,001	893	9,300
02-01-1240FR	1240	0,001	0,001	974	9,800