

TECHNI CONNECT 20



Temperature Operating Range: - 30 / + 700 C°

Hose Features:

- Very high temperature resistance
 - Small bend radius
 - Compressibility: 1:3
-
- External galvanised steel helix protects against abrasion
 - Silicone free
 - Nearly inflammable

Suitable for use in:

- Hot air transfer
- Defence industries
- Glass factory
- Low pressure applications
- Furnace construction
- Iron and steel industries
- Moulding applications
- Shipbuilding industries
- Industrial drying plants

Length:

Up to 203 mm ID – 10-20 metres long

229 mm -820 mm ID – 5-10 metres long

Above 920 mm ID – 5 metres long

PART CODES: SIZES & TECHNICAL SPECIFICATIONS

PRODUCT CODE	INNER DIAMETER	WORKING PRESSURE	VACUUM	BENDING RADIUS	WEIGHT
	<i>mm</i>	<i>bar</i>	<i>bar</i>	<i>mm</i>	<i>gr./mt</i>
20-01-133	133	0,247	0,097	104,0	2,395
20-01-140	140	0,181	0,082	111,5	2,495
20-01-152	152	0,157	0,068	119,0	2,155
20-01-160	160	0,145	0,061	126,5	2,325
20-01-180	180	0,117	0,051	141,5	2,660
20-01-203	203	0,106	0,041	156,5	2,895
20-01-229	229	0,090	0,033	186,5	3,265
20-01-254	254	0,081	0,030	206,5	3,510
20-01-280	280	0,077	0,024	226,5	4,010
20-01-305	305	0,066	0,020	246,5	4,370
20-01-315	315	0,054	0,019	258,5	4,375
20-01-356	356	0,041	0,015	286,5	4,910
20-01-406	406	0,036	0,013	326,5	5,700
20-01-457	457	0,024	0,010	389,0	6,435
20-01-508	508	0,019	0,006	431,5	7,125
20-01-559	559	0,016	0,006	476,5	7,870
20-01-610	610	0,013	0,005	516,5	8,605
20-01-710	710	0,010	0,005	601,5	9,830
20-01-820	820	0,008	0,004	686,5	11,255
20-01-920	920	0,006	0,004	771,5	12,735
20-01-1030	1030	0,004	0,003	842,0	13,425
20-01-1130	1130	0,002	0,003	919,0	14,125
20-01-1240	1240	0,001	0,002	984,0	14,875