

TECHNI CONNECT 21

Operating Temperature Range:

- 30 / + 1100 C°

Features:

- Very high temperature resistance
- Small bend radius
- External steel protects against abrasion
- Flame resistant
- Composite production style



For use in:

- Hot air transfer
- Defence industries
- Glass factory
- Furnace construction
- Iron and steel industries
- Shipbuilding industries

Lengths: 5 metres (10 metres on application)

PART CODES: SIZES & TECHNICAL SPECIFICATIONS

PRODUCT CODE	INNER DIAMETER	WORKING PRESSURE	VACUUM	BENDING RADIUS	WEIGHT
	<i>mm</i>	<i>bar</i>	<i>bar</i>	<i>mm</i>	<i>gr./mt.</i>
21-01-130	130	0,26	1188	76	1,4
21-01-140	140	0,19	1055	85	1,5
21-01-150	150	0,17	930	92	1,6
21-01-160	160	0,162	800	95	1,65
21-01-180	180	0,13	620	110	2,1
21-01-200	200	0,12	500	120	2,2
21-01-225	225	0,106	400	160	2,75
21-01-254	254	0,096	350	175	3,1
21-01-275	275	0,092	270	190	3,55
21-01-300	300	0,08	225	209	3,95
21-01-315	315	0,066	210	220	4,1
21-01-350	350	0,05	175	228	4,55
21-01-400	400	0,038	125	279	6
21-01-450	450	0,03	100	362	6,75
21-01-500	500	0,027	90	398	7,5
21-01-550	550	0,025	75	441	8,5
21-01-600	600	0,022	60	480	9,5
21-01-700	700	0,015	55	563	11
21-01-800	800	0,013	45	641	13
21-01-900	900	0,009	25	724	14,5